

SILKY PEARL DECORATIVE COATING



DESCRIPTION

ATRACTO, is an acrylic emulsion based, silky, gold and silver finish decorative coating containing metallic pigments.

APPLICATION AREA

It is used on walls, plasters, gross concretes and wooden surfaces indoors together with the appropriate primer after floor preparation.

SURFACE PREPARATION

After all kinds of dirt, oil, bloated paints and dust are cleaned from the surfaces it will be applied on, surface defects should be smoothened with SAN DECO ACRYLIC PUTTY INTERIOR and primed with SAN DECO DECOPRIMER.

The Product

Composition	Acrylic Based, Metallic Pigments
Density	1.20 g/cm ³
	10,01 lbs./gallon
Storage Temperature	5 °C + 35 °C 41 °F + 95 °F
Emission Limits of Volatile Organic Compounds (VOC) According to Directive 2004/42/CE	Subcategory: L VOC: 52 g/l (max); Limit Phase : 200 g/l
Theoretical Coverage (Single Coat)	326 – 509 sq. Ft/gallon
	8,0 – 12,5 m ² /L
Weight Per Gallon	10,01 lbs.
Packaging	1 Quart, 1 Gallon

FEATURES

- ATRACTO offers a glittering decorative look due to the metallic pigments it contains.
- Vivid and bright pigments provide a pleasant shine on the surface.
- Due to the strong water vapor permeability, it allows water vapor to be released outside and the surface to breathe.
- It does not harm human health and environment as it is water-based.
- It allows environments of application to smell nice due to its perfume characteristic.

The Application

Dilution	Ready To Use
Surface Preparation	San Deco Acrylic Putty Interior
Primer	San Deco Decoprimer
Application Tools	Trowel, Brush
Touch Dry Time	5-6 Hours
Complete Dry Time	24 Hours
Dry Time Temperature	23 °C - 73.4°F (relative humidity at 50%)
Application Temperature (24 hours during and after the application)	5 °C + 35 °C 41 °F + 95 °F

SAN DECO

Paint Manufacturing & Distribution

Headquarters: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul

Contact: +1 786-224-14-64

APPLICATION INSTRUCTION

- ATRACTO should be mixed homogeneously without being diluted.
- In the first layer of application, ATRACTO is applied with a trowel or brush.
- The second layer is again applied with a trowel or brush and is completed by creating patch patterns with a trowel.
- It is required to wait at least 6 hours between layers.
- It should be paid attention that the ambient temperature should be minimum +5°C/41°F, and maximum +35°C/95°F within 24 hours during and after the application.

DRYING TIME

At 23°C/73.4°F, the touch dry time is 5-6 hours and the complete drying time is 24 hours.

THEORETICAL CONSUMPTION

For one-layer application, depending on the surface smoothness, absorbency and application techniques;

-8,0 - 12,5 m² with 1 lt.

-6.5 - 10.0 m² area is painted with 1 kg.

- Paint consumption for an area of 1 m² is 80 - 125 ml and 110 - 150 gr.

STORAGE

It can be stored in its unopened package, cool and dry environments, protected from direct sunlight at between +5°C/41°F, and +35°C/95°F.



HAZARD STATEMENTS

- H317 May cause an allergic skin reaction

PRECAUTIONARY STATEMENTS

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- EUH208 Contains: chloromethylisothiazolinone and methylisothiazolinone (3:1); 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1); 2-methylisothiazol-3(2H)-one and 1,2-benzisothiazol-3(2H)-one. Includes. May produce an allergic reaction.
- EUH210 Safety data sheet available on request
- EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. DP. 002.US - Rev01 January 2022

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standards of ISO 9001, ISO 14001, ISO 27001, ISO 45001.