

ELASTIC TEXTURED EXTERIOR COATING



DESCRIPTION

RULOTEX is an acrylic emulsion based, long-lasting decorative, textured exterior paint.

APPLICATION AREA

It can be used on the exterior of all kinds of buildings, on surfaces such as black cement plaster, gross concrete and cement sheet, and on interior surfaces if desired, with the appropriate primer for decorative purposes.

SURFACE PREPARATION

After all kinds of dirt, oil, blistered paint and dust are cleaned from the surfaces of application, the surface defects should be smoothed with SAN DECO ACRYLIC PUTTY EXTERIOR.

Prior to application, the surface can be prepared with SAN DECO UNIPRIMER in a color suitable for the selected color, or RULOTEX can be used in place of the plaster by being thinned 30% by volume to achieve a better result.

The Product

Composition	Acrylic Based, Textured
Density	1,41 g/cm ³
	11,76 lbs./gallon
Storage Temperature	5 °C + 35 °C 41 °F + 95 °F
Emission Limits of Volatile Organic Compounds (VOC) According to Directive 2004/42/CE	Subcategory: C VOC: 20 g/l (max); Limit Phase : 40 g/l
Theoretical Coverage (Single Coat)	29 – 41 sq. Ft/gallon
	0,71 – 1,00 m ² /L
Weight Per Gallon	11,76 lbs.
Packaging	3 Gallon

FEATURES

- Due to its elasticity, it is a material that can maintain its elasticity even at low temperatures, it serves as a bridge in cracks formed on the surface;
- It is not affected by cracks that may occur as a result of buildings subsiding.
- It is resistant to UV, colors do not fade.
- It has high alkali resistance.
- It provides complete protection against external weather conditions on the surface on which it is applied.
- Due to the strong water vapor permeability, it allows water vapor to be released outwards and the surface to breathe.
- It is water-based, not harm human health and environment.

The Application

Dilution	5-10% (Clean Water)
Surface Preparation	San Deco Acrylic Putty Exterior
Application Tools	Roller, Brush, Spray
Touch Dry Time	4-6 Hours
Complete Dry Time	24 Hours
Dry Time Temperature	23 °C - 73.4°F (relative humidity at 50%)
Application Temperature (24 hours during and after the application)	5 °C + 35 °C 41 °F + 95 °F

APPLICATION INSTRUCTION

- After primer is applied, RULOTEX is diluted with 5-10% water by volume and applied in one layer by a roller or brush or by spraying.
- If a thick patterned application is desired, the product should be applied without being diluted.
- It should be paid attention that the ambient temperature should be minimum +5°C/41 °F, and maximum +35°C/95 °F within 24 hours during and after the application.

DRYING TIME

At 23°C/73.4°F, the touching time is 4-6 hours and the complete drying time is 24 hours.

THEORETICAL CONSUMPTION

For one-layer application, depending on the surface smoothness, absorbency and application techniques;

-0,71 - 1,00 m² with 1 lt.

STORAGE

It can be stored in its unopened package, cool and dry environments, protected from direct sunlight at between +5°C/41 °F and +35°C/95 °F.



HAZARD STATEMENTS

- H317 May cause an allergic skin reaction.
- H362 May cause harm to breast-fed children

PRECAUTIONARY STATEMENTS

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 - P263 Avoid contact during pregnancy/while nursing
 - P272 Contaminated work clothing should not be allowed out of the workplace.
 - P280 Wear protective gloves/protective clothing/eye protection/face protection.
 - P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 - P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
 - P363 Wash contaminated clothing before reuse.
 - EUH208 Contains: chloromethylisothiazolinone and methylisothiazolinone (3:1); 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1); 2-methylisothiazol-3(2H)-one and 1,2-benzisothiazol-3(2H)-one.includes.May produce an allergic reaction.
 - EUH210 Safety data sheet available on request
 - EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. EP.006.US - Rev01 January 2022

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standards of ISO 9001, ISO 14001, ISO 27001, ISO 45001.